



derek@infracomfort.co.nz
 027 477 5987 or 0800 386 374
 18 Hurunui Lane, RD 1 Taupo 3377

Frameless Series Specifications

- Rated voltage: 240V/50Hz
- Heating element: Carbon crystal or NiCr (FW)
- Wavelength: 8,000-15,000nm
- Surface Temperature: 70-90°C
- Electric Conversion efficiency: 98%
- Life expectancy: >100,000 H
- Front Surface: Powder coated Aluminium
- Colour: Off white semi-gloss/ Black semi gloss
- Frame: no frame
- Ingress protection ratio: IP42
- Overheat protection: yes
- Insulation: fully insulated back
- Fitting: direct to ceiling or wall. Suspension mount optional extra
- Cable length: 2m, rear entry
- Standards: CE-LVD, EMC, RoHS, SAA



* The off-white, low sheen powder coated aluminium is presentable and unobtrusive and may be easily fitted directly to the ceiling or wall. Other colours are available on request.

Model	Wattage	Length (mm)	Width (mm)	Thickness (mm)	Weight (Kg)	Surface Colour
F0606-3	350	595	595	25	4.1	Off white satin
F1006-4	450	1000	595	25	7.8	Off white satin
F1206-5	550	1195	595	25	8.1	Off white satin
F1206-7	700	1195	595	25	9.3	Off white satin
F1206-9	900	1195	595	25	9.3	Off white satin